

API Inquiry: *get_allgiftsa*

Description	Returns gifts, payments, and unposted transactions that match the data file.		
Parameters	scheme	GET	<i>Required.</i> All connection types. Inquiry type indicator.
	action	get_allgiftsa	<i>Required.</i> All connection types. Variable representing the specific inquiry.
	URL	nnn.nnn.n.n	<i>Optional.</i> Direct and DAD only. The URL of the requester, used for reporting. Results will display only if a URL is included.
	dsource	xxxxxxx	<i>Required.</i> Connection pooling servlet only. The key to the client door to the database.
	datafile	Any valid gift column	<i>Required at least one.</i>
		Alias	<i>Optional. Restrict based on alias</i>
Sample Data	<pre><?xml version="1.0" encoding="UTF-8"?> <XMLREQUEST> <RECORD> <IDNUMBER>3</IDNUMBER> </RECORD> </XMLREQUEST></pre>		
Sample Result	<pre><GET_ALLGIFTSA TRANS_TIMESTAMP="07/21/2014 02:09:09 pm" IDNUMBER="3"> <GIFT> <GIFT.IDNUMBER>3</GIFT.IDNUMBER> <GIFT.TABLENAME>GIFT</GIFT.TABLENAME> <GIFT.TRANSNUM>894634</GIFT.TRANSNUM> <GIFT.TRANTYPE>D</GIFT.TRANTYPE> <GIFT.GIFTAMOUNT>75.00</GIFT.GIFTAMOUNT> <GIFT.BALANCE>.00</GIFT.BALANCE> <GIFT.DATE>04/24/2014</GIFT.DATE> <GIFT.APPEALCODE>1</GIFT.APPEALCODE> <GIFT.FUNDCODE>1</GIFT.FUNDCODE> <GIFT.GIFTTYPE>1</GIFT.GIFTTYPE> </GIFT> <GIFT> <GIFT.IDNUMBER>3</GIFT.IDNUMBER> <GIFT.TABLENAME>BATCHDETAIL</GIFT.TABLENAME> <GIFT.TRANSNUM>505051</GIFT.TRANSNUM> <GIFT.TRANTYPE>D</GIFT.TRANTYPE> <GIFT.GIFTAMOUNT>.00</GIFT.GIFTAMOUNT> <GIFT.PAYAMOUNT>5.00</GIFT.PAYAMOUNT> <GIFT.DATE>07/22/2013</GIFT.DATE> <GIFT.APPEALCODE>APPEAL</GIFT.APPEALCODE> <GIFT.FUNDCODE>ARTS</GIFT.FUNDCODE> <GIFT.GIFTTYPE>CHK</GIFT.GIFTTYPE> </GIFT> </GET_ALLGIFTSA></pre>		
Additional Reading			

API Inquiry: *get_allgiftsa*

Reference	
-----------	--

API Inquiry: `get_allgiftsa`

Connection Pooling	http://webapps.pledgemaker.com/test/proc?d_source=12345678&scheme=GET&action=get_allgiftsa&datafile=
Data Access Descriptor (DAD)	<a 1.0"="" ?><xmlrequest><record><idnumber>3<="" encoding="UTF-8" href="http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_allgiftsa&data=<?xml version=" idnumber><="" record><="" xmlrequest>"="">http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_allgiftsa&data=<?xml version="1.0" encoding="UTF-8"?><XMLREQUEST><RECORD><IDNUMBER>3</IDNUMBER></RECORD></XMLREQUEST>
Direct Connection	<pre> set serveroutput on; declare vScheme varchar2(100) := 'GET'; vAction varchar2(200) := 'xml_pm.get_allgiftsa'; vURL varchar2(100) := '128.168.0.1'; vXML varchar2(10000); rval_clob CLOB; begin owa.num_cgi_vars := 0; vXML := '<?xml version="1.0" encoding="UTF-8"?>' CHR(10) ' <XMLREQUEST>' CHR(10) ' <RECORD>' CHR(10) ' <idnumber>3</ idnumber >' CHR(10) ' </RECORD>' CHR(10) ' </XMLREQUEST>'; rval_clob := NULL; apiwrap.all_traffic(vScheme, vAction, vURL, vXML, rval_clob); IF (rval_clob IS NOT NULL) THEN dbms_output.put_line(substr(rval_clob,1,200)); dbms_output.put_line(substr(rval_clob,201,200)); dbms_output.put_line(substr(rval_clob,401,200)); dbms_output.put_line(substr(rval_clob,601,200)); dbms_output.put_line(substr(rval_clob,801,200)); END IF; end; </pre>