

API Inquiry: `get_codesa`

Description	Given a code table name it will return a list of codes within that table. Will return only code and description.		
Parameters	scheme	GET	<i>Required.</i> All connection types. Inquiry type indicator.
	action	get_codesa	<i>Required.</i> All connection types. Variable representing the specific inquiry.
	URL	nnn.nnn.n.n	<i>Optional.</i> Direct and DAD only. The URL of the requester, used for reporting. Results will display only if a URL is included.
	dsource	xxxxxxx	<i>Required.</i> Connection pooling servlet only. The key to the client door to the database.
Search Criteria	datafile	TABLENAME	<i>Required.</i> Selects the code table.
Sample Data	<pre><?xml version="1.0" encoding="UTF-8"?> <XMLREQUEST> <RECORD> <TABLENAME>ACTIONS</TABLENAME > </RECORD> </XMLREQUEST></pre>		
Sample Result	<pre><?xml version="1.0"?> <GET_CODES TABLENAME="ACTIONS" TRANS_TIMESTAMP="07/18/2014 11:41:05Am"> <PMCODE> <ACTIONS.CODE>MAIL</ACTIONS.CODE> <ACTIONS.DESCRPTION>Mailing</ACTIONS.DESCRPTION> </PMCODE> </GET_CODES></pre>		
Additional Reading	get_codes		
Reference			

API Inquiry: `get_codesa`

Connection Pooling	<a href="http://webapps.softrek.com/api/proc?d_source=12345678&scheme=GET&action=get_codesa&<attached_XML_doc>">http://webapps.softrek.com/api/proc?d_source=12345678&scheme=GET&action=get_codesa&<attached_XML_doc>
Data Access Descriptor (DAD)	<a href="http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_codesa&data=<?xml version='1.0' encoding='UTF-8'?><XMLREQUEST><RECORD><TABLENAME>ACTIONS</TABLENAME></RECORD></XMLREQUEST>">http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_codesa&data=<?xml version='1.0' encoding='UTF-8'?><XMLREQUEST><RECORD><TABLENAME>ACTIONS</TABLENAME></RECORD></XMLREQUEST>
Direct Connection	<pre>set serveroutput on; declare vScheme varchar2(100) := 'GET'; vAction varchar2(200) := 'xml_pm.get_codesa'; vURL varchar2(100) := '128.168.0.1'; vXML varchar2(10000); rval_clob CLOB; begin owa.num_cgi_vars := 0; vXML := '<?xml version="1.0" encoding="UTF-8"?>' CHR(10) ' <XMLREQUEST>' CHR(10) ' <RECORD>' CHR(10) ' <TABLENAME>ACTIONS</TABLENAME>' CHR(10) ' </RECORD>' CHR(10) ' </XMLREQUEST>'; rval_clob := NULL; apiwrap.all_traffic(vScheme, vAction, vURL, vXML, rval_clob); IF (rval_clob IS NOT NULL) THEN dbms_output.put_line(substr(rval_clob,1,200)); dbms_output.put_line(substr(rval_clob,201,200)); dbms_output.put_line(substr(rval_clob,401,200)); dbms_output.put_line(substr(rval_clob,601,200)); dbms_output.put_line(substr(rval_clob,801,200)); END IF; end;</pre>