

API Inquiry: *get_eventgifts*

Description	Returns event gift totals broken down by donor. Includes full payment information.			
Parameters	scheme	GET	<i>Required.</i> All connection types. Inquiry type indicator.	
	action	get_eventgifts	<i>Required.</i> All connection types. Variable representing the specific inquiry.	
	URL	nnn.nnn.n.n	<i>Optional.</i> Direct and DAD only. The URL of the requester, used for reporting. Results will display only if a URL is included.	
	dsource	xxxxxxx	<i>Required.</i> Connection pooling servlet only. The key to the client door to the database.	
	datafile	idnumber	optional	restricts to payments with this idnumber
		groupid	optional, but must be combined with name_id	restricts regname (participant) selection (applied to regname.groupid)
		name_id	optional, but must be combined with groupid	restricts regname (participant) selection (applied to regname.name_id)
		regnameid	<i>REQUIRED</i>	restricts regname (participant) selection (applied to regname.transnum)
paydate_start		optional	restricts to payments with paydate on or after this date	
paydate_end		optional	restricts to payments with paydate on or before this date	
Sample Data	<pre><?xml version="1.0" encoding="UTF-8"?> <XMLREQUEST> <RECORD> <REGNAMEID>2589</REGNAMEID> </RECORD> </XMLREQUEST></pre>			
Sample Result	<pre></GET_EVENTGIFTS> <PROSPECT> <PROSPECT.IDNUMBER>11321076</PROSPECT.IDNUMBER> <PROSPECT.FIRST>John</PROSPECT.FIRST> <PROSPECT.LAST>Tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>1102</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>69</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>1033</PROSPECT.POSTEDGIFTPAYTOTAL> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>0</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> <PROSPECT> <PROSPECT.IDNUMBER>11321080</PROSPECT.IDNUMBER> <PROSPECT.FIRST>Johnfriend3</PROSPECT.FIRST> <PROSPECT.LAST>Tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>50</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>0</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>50</PROSPECT.POSTEDGIFTPAYTOTAL></pre>			

API Inquiry: `get_eventgifts`

	<pre> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>0</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> <PROSPECT> <PROSPECT.IDNUMBER>11321246</PROSPECT.IDNUMBER> <PROSPECT.FIRST>johnfriend6unpostedgift</PROSPECT.FIRST> <PROSPECT.LAST>tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>25</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>0</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>0</PROSPECT.POSTEDGIFTPAYTOTAL> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>25</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> <PROSPECT> <PROSPECT.IDNUMBER>11321079</PROSPECT.IDNUMBER> <PROSPECT.FIRST>Johnfriend2</PROSPECT.FIRST> <PROSPECT.LAST>Tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>50</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>0</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>50</PROSPECT.POSTEDGIFTPAYTOTAL> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>0</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> <PROSPECT> <PROSPECT.IDNUMBER>11321078</PROSPECT.IDNUMBER> <PROSPECT.FIRST>Johnfriend1</PROSPECT.FIRST> <PROSPECT.LAST>Tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>50</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>0</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>50</PROSPECT.POSTEDGIFTPAYTOTAL> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>0</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> <PROSPECT> <PROSPECT.IDNUMBER>11321081</PROSPECT.IDNUMBER> <PROSPECT.FIRST>Johnfriend4</PROSPECT.FIRST> <PROSPECT.LAST>Tomtest</PROSPECT.LAST> <PROSPECT.PAYTOTAL>50</PROSPECT.PAYTOTAL> <PROSPECT.POSTEDREGPAYTOTAL>0</PROSPECT.POSTEDREGPAYTOTAL> <PROSPECT.POSTEDGIFTPAYTOTAL>50</PROSPECT.POSTEDGIFTPAYTOTAL> <PROSPECT.UNPOSTEDREGPAYTOTAL>0</PROSPECT.UNPOSTEDREGPAYTOTAL> <PROSPECT.UNPOSTEDGIFTPAYTOTAL>0</PROSPECT.UNPOSTEDGIFTPAYTOTAL> </PROSPECT> </GET_EVENTGIFTS> </pre>
Additional Reading	
Reference	

API Inquiry: `get_eventgifts`

Connection Pooling	http://webapps.pledgemaker.com/test/proc?d_source=12345678&scheme=GET&action=get_eventgifts&datafile=
Data Access Descriptor (DAD)	<a 1.0"="" ?><xmlrequest><record><regnameid>2589<="" encoding="UTF-8" href="http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_eventgifts&data=<?xml version=" record><="" regnameid><="" xmlrequest>"="">http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&url=128.168.0.1&action=get_eventgifts&data=<?xml version="1.0" encoding="UTF-8"?><XMLREQUEST><RECORD><REGNAMEID>2589</REGNAMEID></RECORD></XMLREQUEST>
Direct Connection	<pre> set serveroutput on; declare vScheme varchar2(100) := 'GET'; vAction varchar2(200) := 'xml_pm.get_eventgifts'; vURL varchar2(100) := '128.168.0.1'; vXML varchar2(10000); rval_clob CLOB; begin owa.num_cgi_vars := 0; vXML := '<?xml version="1.0" encoding="UTF-8"?>' CHR(10) ' <XMLREQUEST>' CHR(10) ' <RECORD>' CHR(10) ' <REGNAMEID>2589</REGNAMEID>' CHR(10) ' </RECORD>' CHR(10) ' </XMLREQUEST>'; rval_clob := NULL; apiwrap.all_traffic(vScheme, vAction, vURL, vXML, rval_clob); IF (rval_clob IS NOT NULL) THEN dbms_output.put_line(substr(rval_clob,1,200)); dbms_output.put_line(substr(rval_clob,201,200)); dbms_output.put_line(substr(rval_clob,401,200)); dbms_output.put_line(substr(rval_clob,601,200)); dbms_output.put_line(substr(rval_clob,801,200)); END IF; end; </pre>