

# API Inquiry: get\_sumeventgift

<b>Description</b>	Given an event – return total gift payments for the event.		
<b>Parameters</b>	<b>scheme</b>	GET	<i>Required.</i> All connection types. Inquiry type indicator.
	<b>action</b>	get_sumeventgift	<i>Required.</i> All connection types. Variable representing the specific inquiry.
	<b>URL</b>	nnn.nnn.n.n	<i>Optional.</i> Direct and DAD only. The URL of the requester, used for reporting. Results will display only if a URL is included.
	<b>dsource</b>	xxxxxxxx	<i>Required.</i> Connection pooling servlet only. The key to the client door to the database.
	<b>datafile</b>	event	<i>Required.</i> Limits selection to the specific event.
<b>Sample Data</b>	<pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt; &lt;XMLREQUEST&gt; &lt;RECORD&gt; &lt;EVENT&gt;EVENT1&lt;/EVENT&gt; &lt;/RECORD&gt; &lt;/XMLREQUEST&gt;</pre>		
<b>Sample Result</b>	<pre>&lt;?xml version="1.0" ?&gt; &lt;GET_SUMEVENTGIFT TRANS_TIMESTAMP="07/18/2014 04:20:56 pm" EVENT="EVENT1"&gt; &lt;EVENT&gt;&lt;EVENTS.CODE&gt;EVENT1&lt;/EVENTS.CODE&gt; &lt;EVENTS.GIFTTOTAL&gt;8321&lt;/EVENTS.GIFTTOTAL&gt; &lt;EVENTS.GIFTCOUNT&gt;71&lt;/EVENTS.GIFTCOUNT&gt; &lt;/EVENT&gt; &lt;/GET_SUMEVENTGIFT&gt;</pre>		
<b>Additional Reading</b>			
<b>Reference</b>	E460019		

# API Inquiry: get\_sumeventgift

<b>Connection Pooling</b>	<a href="https://webapps.softrek.com/testprod/api/proc?dsource=12345678&amp;scheme=GET&amp;action=get_sumeventgift&amp;datafile=">https://webapps.softrek.com/testprod/api/proc?dsource=12345678&amp;scheme=GET&amp;action=get_sumeventgift&amp;datafile=</a>
<b>Data Access Descriptor (DAD)</b>	
<b>Direct Connection</b>	<pre> set serveroutput on; declare vScheme varchar2(100) := 'GET'; vAction varchar2(200) := 'xml_pm.get_sumeventgift'; vURL varchar2(100) := '128.168.0.1'; vXML varchar2(10000); rval_clob CLOB; begin owa.num_cgi_vars := 0; vXML := '&lt;?xml version="1.0" encoding="UTF-8"?&gt;'    CHR(10)    ' &lt;XMLREQUEST&gt;'    CHR(10)    ' &lt;RECORD&gt;'    CHR(10)    ' &lt;EVENT&gt;EVENT1&lt;/EVENT &gt;'    CHR(10)    ' &lt;/RECORD&gt;'    CHR(10)    ' &lt;/XMLREQUEST&gt;'; rval_clob := NULL; apiwrap.all_traffic(vScheme, vAction, vURL, vXML, rval_clob); IF (rval_clob IS NOT NULL) THEN dbms_output.put_line(substr(rval_clob,1,200)); dbms_output.put_line(substr(rval_clob,201,200)); dbms_output.put_line(substr(rval_clob,401,200)); dbms_output.put_line(substr(rval_clob,601,200)); dbms_output.put_line(substr(rval_clob,801,200)); END IF; end; </pre>