

# API Inquiry: get\_sumpayamountind

<b>Description</b>	Given an alias or appealcode – returns the sum of payments for the prospect, appealcode or combination.		
<b>Parameters</b>	<b>scheme</b>	GET	<i>Required.</i> All connection types. Inquiry type indicator.
	<b>action</b>	get_sumpayamountind	<i>Required.</i> All connection types. Variable representing the specific inquiry.
	<b>URL</b>	nnn.nnn.n.n	<i>Optional.</i> Direct and DAD only. The URL of the requester, used for reporting. Results will display only if a URL is included.
	<b>dsource</b>	xxxxxxxx	<i>Required.</i> Connection pooling servlet only. The key to the client door to the database.
	<b>datafile</b>	appealcode alias	<i>Optional.</i> Selects only payments with this appealcode. <i>Optional.</i> Selects only payments belonging to prospect(s) with this alias.
<b>Sample Data</b>	<pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt; &lt;XMLREQUEST&gt; &lt;RECORD&gt; &lt;IDNUMBER&gt;ALIAS123&lt;/IDNUMBER&gt; &lt;/RECORD&gt; &lt;/XMLREQUEST&gt;</pre>		
<b>Sample Result</b>	<pre>&lt;?xml version="1.0" ?&gt; - &lt;GET_SUMPAYAMOUNTIND TRANS_TIMESTAMP="01/19/2007 12:14:23 pm" ALIAS="ALIAS123"&gt; - &lt;PAYMENT&gt; - &lt;SUM_PAYAMOUNT&gt;150&lt;/SUM_PAYAMOUNT&gt;   &lt;/PAYMENT&gt; &lt;/GET_SUMPAYAMOUNTIND&gt;</pre>		
<b>Additional Reading</b>	Payment, relevant API connection documents, <a href="#">get_sumpayamountgroup</a>		
<b>Reference</b>	E430034		

# API Inquiry: get\_sumpayamountind

<b>Connection Pooling</b>	<a href="http://webapps.pledgemaker.com/test/proc?d_source=12345678&amp;scheme=GET&amp;action=get_sumpayamountind&amp;&lt;attached_XML_doc&gt;">http://webapps.pledgemaker.com/test/proc?d_source=12345678&amp;scheme=GET&amp;action=get_sumpayamountind&amp;&lt;attached_XML_doc&gt;</a>
<b>Data Access Descriptor (DAD)</b>	<a 1.0"="" ?&gt;&lt;xmlrequest&gt;&lt;record&gt;&lt;alias&gt;alias123&lt;="" alias&gt;&lt;="" encoding="UTF-8" href="http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&amp;url=128.168.0.1&amp;action=get_sumpayamountind&amp;data=&lt;?xml version=" record&gt;&lt;="" xmlrequest&gt;"="">http://pm-devel/pls/testv440/apiwrap.h_traffic?scheme=GET&amp;url=128.168.0.1&amp;action=get_sumpayamountind&amp;data=&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;XMLREQUEST&gt;&lt;RECORD&gt;&lt;ALIAS&gt;ALIAS123&lt;/ALIAS&gt;&lt;/RECORD&gt;&lt;/XMLREQUEST&gt;</a>
<b>Direct Connection</b>	<pre> set serveroutput on;  declare vScheme varchar2(100) := 'GET'; vAction varchar2(200) := 'xml_pm.get_sumpayamountind'; vURL varchar2(100) := '128.168.0.1'; vXML varchar2(10000); rval_clob CLOB; begin owa.num_cgi_vars := 0; vXML := '&lt;?xml version="1.0" encoding="UTF-8"?&gt;'    CHR(10)    ' &lt;XMLREQUEST&gt;'    CHR(10)    ' &lt;RECORD&gt;'    CHR(10)    ' &lt;ALIAS&gt;ALIAS123&lt;/ALIAS&gt;'    CHR(10)    ' &lt;/RECORD&gt;'    CHR(10)    ' &lt;/XMLREQUEST&gt;'; rval_clob := NULL; apiwrap.all_traffic(vScheme, vAction, vURL, vXML, rval_clob); IF (rval_clob IS NOT NULL) THEN dbms_output.put_line(substr(rval_clob,1,200)); dbms_output.put_line(substr(rval_clob,201,200)); dbms_output.put_line(substr(rval_clob,401,200)); dbms_output.put_line(substr(rval_clob,601,200)); dbms_output.put_line(substr(rval_clob,801,200)); END IF; end; </pre>